



| | | | |
|----------------------------|---|--|---|
| Project | : | Location | : |
| Device Location | : | | |
| Brand | : | REXLiTE [®] | |
| Origin | : | Taiwan | |
| Color | : | Black / Aluminum | |
| Beam Angle | : | Linear Light, Flood, Embedded / Suspension | |
| Dimension | : | L 509 × W13.5 × H14.2 mm | |
| | | L1,009 × W13.5 × H14.2 mm | |
| | | L1,509 × W13.5 × H14.2 mm | |
| | | L2,009 × W13.5 × H14.2 mm | |
| LED Source | : | NICHIA LED | |
| LED Specs | : | Ra ≥ 90 LM80 2,700K-5,000K R9 > 50 | |
| Color Tolerance Adjustment | : | SDCM ≤ 3 | |
| Luminous Flux | : | 400 Lm / 800 Lm / 1,200 Lm / 1,600 Lm | |
| Power Consumption | : | 3.5W / 7W / 10.5W / 14W | |
| Material | : | Aluminum, PC | |
| Finish | : | Anodizing | |
| Bore Dimension | : | L × W13.5 × H > 23 mm | |
| Power Supplier | : | 0.15A / 0.35A / 0.7A / 1.4A Constant Current | |
| | | External power supply | |
| | | CE Compliance | |
| | | Noryl UL94V-0 | |
| Note | : | Heat Sink Temp. < 65°C | |